

Piquages express PS à 90°

Dimensions (mm)		Galva standard		Galva avec joints		Aluminium standard	
Ø D	Ø d	REF	CODE	REF	CODE	REF	CODE
80	80	PS 80/80	547 102	-	-	-	-
80	125	PS 80/125	543 179	-	-	-	-
80	160	PS 80/160	547 112	-	-	-	-
100	100	PS 100/100	533 215	-	-	-	-
100	125	PS 100/125	523 968	-	-	-	-
100	160	PS 100/160	533 199	-	-	-	-
100	200	PS 100/200	533 198	-	-	-	-
100	250	PS 100/250	533 197	-	-	-	-
100	315	PS 100/315	533 196	-	-	-	-
100	355	PS 100/355	533 242	-	-	-	-
100	400	PS 100/400	533 322	-	-	-	-
100	450	PS 100/450	533 323	-	-	-	-
100	500	PS 100/500	533 324	-	-	-	-
125	125	PS 125/125	523 800	PS 125/125 J	530 000	PS 125/125 AL	523 088
125	160	PS 125/160	523 801	PS 125/160 J	530 001	PS 125/160 AL	523 089
125	200	PS 125/200	523 802	PS 125/200 J	530 002	PS 125/200 AL	523 090
125	250	PS 125/250	523 803	PS 125/250 J	530 003	PS 125/250 AL	523 091
125	315	PS 125/315	533 433	PS 125/315-355 J	533 388	-	-
125	355 à 400	PS 125/355-400	523 813	-	-	-	-
125	450	PS 125/450	523 210	PS 125/400-450 J	530 005	-	-
125	500	PS 125/500	533 435	PS 125/500 J	533 390	-	-
125	560	PS 125/560	533 406	PS 125/560 J	533 391	-	-
125	630	PS 125/630	533 407	PS 125/630 J	533 392	-	-
160	160	PS 160/160	523 805	PS 160/160 J	530 006	PS 160/160 AL	523 093
160	200	PS 160/200	523 806	PS 160/200 J	530 007	PS 160/200 AL	523 094
160	250	PS 160/250	523 807	PS 160/250 J	530 008	PS 160/250 AL	523 095
160	315	PS 160/315	533 408	PS 160/315 J	533 393	PS 160/315 AL	533 383
160	355 à 400	PS 160/355-400	523 815	PS 160/355-400 J	530 009	-	-
160	450	PS 160/450	523 192	PS 160/450 J	530 010	-	-
160	500	PS 160/500	533 425	PS 160/500 J	533 395	-	-
160	560	PS 160/560	533 426	PS 160/560 J	533 396	-	-
160	630	PS 160/630	533 427	PS 160/630 J	533 397	-	-
200	200	PS 200/200	523 194	PS 200/200 J	530 011	PS 200/200 AL	533 211
200	250	PS 200/250	523 195	PS 200/250 J	530 012	PS 200/250 AL	523 384
200	315	PS 200/315	533 436	PS 200/315 J	533 493	PS 200/315 AL	533 513
200	355 à 400	PS 200/355-400	523 197	PS 200/355-400 J	530 013	PS 200/355-400 AL	533 702
200	450	PS 200/450	523 199	PS 200/450 J	530 014	-	-
200	500	PS 200/500	533 438	PS 200/500 J	533 495	-	-
200	560	PS 200/560	533 439	PS 200/560 J	533 496	-	-
200	630	PS 200/630	533 449	PS 200/630 J	533 497	-	-
250	250	PS 250/250	533 200	PS 250/250 J	530 015	PS 250/250 AL	533 686
250	315	PS 250/315	533 201	PS 250/315 J	530 016	PS 250/315 AL	533 687
250	355 à 400	PS 250/355-400	533 202	PS 250/355-400 J	530 017	PS 250/355-400 AL	543 187
250	450	PS 250/450	533 204	PS 250/450 J	530 018	PS 250/450 AL	543 208
250	500	PS 250/500	533 451	PS 250/500 J	533 499	-	-
250	560	PS 250/560	533 452	PS 250/560 J	533 511	-	-
250	630	PS 250/630	533 453	PS 250/630 J	533 512	-	-
250	710	PS 250/710	543 533	-	-	-	-
315	315	PS 315/315	533 206	PS 315/315 J	530 019	PS 315/315 AL	533 689
315	355 à 400	PS 315/355-400	533 207	PS 315/355-400 J	530 020	PS 315/355-400 AL	533 690
315	450	PS 315/450	533 209	PS 315/450 J	530 021	PS 315/450 AL	533 692
315	500	PS 315/500	533 459	PS 315/500 J	533 527	PS 315/500 AL	533 376
315	560	PS 315/560	533 210	PS 315/560 J	530 022	-	-
315	630	PS 315/630	533 491	PS 315/630 J	533 528	-	-
315	710	PS 315/710	543 174	-	-	-	-
355	355	PS 355/355	543 308	PS 355/355 J	530 023	-	-
355	400	PS 355/400	543 038	PS 355/400 J	530 024	-	-
355	450	PS 355/450	543 046	PS 355/450 J	530 025	-	-
355	500	PS 355/500	543 055	PS 355/500 J	530 026	-	-
355	560	PS 355/560	543 047	PS 355/560 J	530 027	-	-
355	630	PS 355/630	543 309	PS 355/630 J	530 028	-	-
355	710	PS 355/710	543 249	-	-	-	-
355	800	PS 355/800	543 528	-	-	-	-
400	400	PS 400/400	543 071	PS 400/400 J	530 029	-	-
400	450	PS 400/450	543 023	PS 400/450 J	530 030	-	-
400	500	PS 400/500	543 008	PS 400/500 J	530 031	-	-
400	560	PS 400/560	543 310	PS 400/560 J	530 032	-	-
400	630	PS 400/630	533 745	PS 400/630 J	530 033	-	-
400	710	PS 400/710	543 209	-	-	-	-
400	800	PS 400/800	543 534	-	-	-	-


Accessoires de réseaux

Piquages express PS à 90°

Dimensions (mm)		Galva standard		Galva avec joints	
Ø D	Ø d	REF	CODE	REF	CODE
450	450	PS 450/450	543 311	PS 450/450 J	530 034
450	500	PS 450/500	543 037	PS 450/500 J	530 035
450	560	PS 450/560	543 312	PS 450/560 J	530 036
450	630	PS 450/630	543 313	PS 450/630 J	530 037
450	710	PS 450/710	543 360	-	-
450	800	PS 450/800	543 435	-	-
500	500	PS 500/500	533 654	PS 500/500 J	530 038
500	560	PS 500/560	543 314	PS 500/560 J	530 039
500	630	PS 500/630	543 036	PS 500/630 J	530 040
500	710	PS 500/710	533 035	-	-
500	800	PS 500/800	543 535	-	-
560	560	PS 560/560	543 315	-	-
560	630	PS 560/630	523 203	-	-
560	710	PS 560/710	533 237	-	-
560	800	PS 560/800	543 026	-	-
630	630	PS 630/630	543 316	-	-
630	710	PS 630/710	533 036	-	-
630	800	PS 630/800	543 401	-	-

Piquages express PS à 45°

Dimensions (mm)		Galva standard	
Ø D	Ø d	REF	CODE
125	125	PS 125/125-45	543 786
125	160	PS 125/160-45	543 683
125	200	PS 125/200-45	543 684
125	250	PS 125/250-45	543 685
125	315	PS 125/315-45	533 706
125	355	PS 125/355-45	543 514
125	400	PS 125/400-45	524 801
160	160	PS 160/160-45	543 847
160	200	PS 160/200-45	543 860
160	250	PS 160/250-45	543 849
160	315	PS 160/315-45	543 478
160	355	PS 160/355-45	543 431
160	400	PS 160/400-45	543 479
200	200	PS 200/200-45	543 520
200	250	PS 200/250-45	533 707
200	315	PS 200/315-45	547 111
200	355	PS 200/355-45	543 432
200	400	PS 200/400-45	533 705
200	500	PS 200/500-45	543 715
200	630	PS 200/630-45	547 106
250	250	PS 250/250-45	543 447
250	315	PS 250/315-45	543 743
250	355	PS 250/355-45	543 513
250	400	PS 250/400-45	543 511
250	500	PS 250/500-45	547 148
250	630	PS 250/630-45	533 243
315	315	PS 315/315-45	547 116
315	355	PS 315/355-45	543 433
315	400	PS 315/400-45	543 744
315	500	PS 315/500-45	543 522
315	630	PS 315/630-45	543 521
355	355	PS 355/355-45	547 174
355	400	PS 355/400-45	543 524
355	500	PS 355/500-45	543 527
355	630	PS 355/630-45	547 149
400	400	PS 400/400-45	533 244
400	450	PS 400/450-45	533 245
400	500	PS 400/500-45	543 426
400	560	PS 400/560-45	543 518
400	630	PS 400/630-45	543 592
450	450	PS 450/450-45	547 176
450	500	PS 450/500-45	533 246
450	560	PS 450/560-45	547 140
450	630	PS 450/630-45	547 128



Piquages plats à 90°

Dimensions (mm)		Galva standard	
Ø D		REF	CODE
80		PP 80	533 579
100		PP 100	533 577
125		PP 125	523 281
160		PP 160	523 282
200		PP 200	523 283
250		PP 250	523 284
315		PP 315	523 285
355		PP 355	533 145
400		PP 400	533 575
450		PP 450	524 100
500		PP 500	523 984
560		PP 560	543 048
630		PP 630	533 576
710		PP 710	524 098
800		PP 800	524 099

Piquages plats à 45°

Dimensions (mm)		Galva standard	
Ø D		REF	CODE
80		PP 80-45	544 903
100		PP 100-45	543 716
125		PP 125-45	533 582
160		PP 160-45	533 583
200		PP 200-45	533 581
250		PP 250-45	533 578
315		PP 315-45	533 708
355		PP 355-45	533 580
400		PP 400-45	547 150
450		PP 450-45	533 398
500		PP 500-45	547 146