

Syl-Lighter LED Round - 3,000K lamp

Syl-Lighter 195 LED 15W WW

3031602



Range Features

- Syl-lighter Round is available in 3 different body sizes: 165mm, 195mm & 220mm
- High lumen output - up to 1,742lm
- High efficiency - up to 80.9lm
- Choice of 3,000K warm white or 4,000K neutral white colour temperature
- Small recessed depth (<60mm)



PRODUCT OVERVIEW

Beam angle(°)	74
Certifications	F-mark
Colour temperature (K)	3000
Colour	White Bezel
CRI (Ra)	80
EAN code	8711971316022
Luminous flux (lm)	1182
Housing	Aluminium
IK rating	IK02
IP rating	IP44
Lamps	High quality LED
Light colour	Warm white
LOR (%)	100
Mount	Ceiling recessed
Ordering number	3031602
Efficacy (Rated) (lm/w)	79
Average life (Rated) (h)	50000
Technology	LED
Voltage (V)	220 - 240
Compatible dimmers	Leading / trailing edge
Included lamp	Integrated LED
Compatible with bulbs of energy class:	A++ A+ A

DATA TABLE

General data

Average life (Nominal) (h)	50000
Certifications	F-mark
Control gear availability	External
Control gear type	Electronic

Syl-Lighter LED Round - 3,000K lamp

Syl-Lighter 195 LED 15W WW

3031602

EAN code	8711971316022
Environment	Interior
General application	Hospitality; Office ; Logistics & Industry
Housing	Aluminium
Mount	Ceiling recessed
Ordering number	3031602
Range features	Syl-lighter Round is available in 3 different body sizes: 165mm, 195mm & 220mm High lumen output - up to 1,742lm High efficiency - up to 80.9lm Choice of 3,000K warm white or 4,000K neutral white colour temperature Small recessed depth (<60mm)
Product name	Syl-Lighter 195 LED 15W WW
Average life (Rated) (h)	50000
Technology	LED
Sales pack quantity	1
Compatible dimmers	Leading / trailing edge
E-number FI	4270164
Compatible with bulbs of energy class:	A++ A+ A

Optical data

Beam angle(°)	74
Colour temperature (K)	3000
CRI (Ra)	80
Distribution type	Direct - Symmetric
Luminous flux (lm)	1182
Light colour	Warm white
LOR (%)	100

Physical data

Colour	White Bezel
Cutout diameter (mm)	Ø175
Cutout shape	Round
Diameter (mm)	195
Diffuser finish	Opal
Diffuser material	Polycarbonate
Height (mm)	51
IK rating	IK02
IP rating	IP44
Lamp included	Integrated
Length (mm)	Ø195
Recessed depth (mm)	51
Reflector finish	Smooth

Syl-Lighter LED Round - 3,000K lamp

Syl-Lighter 195 LED 15W WW


3031602

Weight (kg)	0.95
Width (mm)	Ø195
Included lamp	Integrated LED
Outer package dimensions (L x W x H) (cm)	61.00 x 41.40 x 31.50
Single package dimensions (L x W x H) (cm)	19.70 x 19.70 x 10.80


Electrical data

Drive current (mA)	350
Electrical protection	Class II
Glow wire test	960
Lamps	High quality LED
Number of heads	1
Efficacy (Rated) (lm/w)	79
T Class max (°C)	-1
T Class min (°C)	-1
Total number of lamps	1
Total power consumption (W)	15
Transformer availability	Included
Transformer mounting	Remote
Voltage (V)	220 - 240

PHOTOMETRY



TECHNICAL DRAWINGS



Syl-Lighter LED Round - 3,000K lamp

Syl-Lighter 195 LED 15W WW

3031602

Lumiance 3031602

 This luminaire contains built in LED lamps.

 } **LED**

The lamps cannot be changed in the luminaire.

874/2012 

 This luminaire contains built in LED lamps.

 } **LED**

The lamps cannot be changed in the luminaire.

Lumiance 3031602  874/2012